

# APPENDIX

## SPECIFICATIONS

LCD Panel	Driving system	TFT Color LCD
	Size	23.6"
	Pixel pitch	0.2715mm(H) x 0.2715mm(V)
Video	H-Frequency	24KHz – 83KHz
	V-Frequency	56 – 75Hz
Display Colors		16.7M Colors
Max. Resolution		1920 x 1080 @60Hz
Plug & Play		VESA DDC2B™, DPMS
Power consumption	ON Mode	46W (Typical)
	Power Saving Mode	≤1W
	OFF Mode	≤0.5W
Audio output		Rated Power 1.0W rms (Per channel)
Input Terminal		VGA
		DVI, HDMI (optional)
Maximum Screen Size		Hor. : 521.28mm
		Ver. : 293.22mm
Power Source		100~240VAC, 50±3Hz, 60±3Hz
Environmental Considerations		Operating Temp: 5° to 35°C
		Storage Temp.: -20° to 60°C
		Operating Humidity: 20% to 85%
Dimensions		555.6 (W) x 415.35(H) x 166.1(D) mm
		21.9 "(W)×16.4 "(H)×6.5 "(D)
Weight (NW)		5.0 kg(11.0 lb)

\*\*\* The above specification is subject to actual product specification and is subject to change without prior notice.

### NOTES:

The Maximum Resolution will depends on the display card supporting. Related issue can refer to [www.hannsg.com](http://www.hannsg.com) FAQ section.